

# PRO-12SW-LS

## 12" LANDSCAPE SUBWOOFER

Part #1063141



### HIGH PERFORMANCE OUTDOOR AUDIO

With a long-throw 12" IMG woofer, the Pro-12SW-LS landscape subwoofer uses the same high performance acoustic design philosophies of our legendary indoor products, bringing the world's most dynamic, powerful, detailed sound to your outdoor living space.

### BIG SUB PERFORMANCE, SMALL SUB AESTHETICS

The full burial design allows for large cabinet volume necessary for low extension and high output, while remaining hidden in its environment. This allows for a superior listening experience while maintaining a high end, modern look in today's finest landscapes and outdoor living spaces.

### DUAL VOICE COIL DESIGN FOR GREAT SOUNDING 70V/100V

For distributed line applications, the Pro-12SW-LS uses a transformerless dual voice coil design for 70V/100V operation. Since transformers severely limit a subwoofer's low frequency capabilities, this unique design is the perfect solution when building a great sounding commercial or large residential system. This design also allows for high performance low impedance operation as well: 8 ohm stereo or 4 ohm mono for the ultimate in system flexibility.

### ALL-WEATHER DURABILITY

A rustproof aluminum top cap and a high impact, polyethylene cabinet provides the utmost in all-weather capability, while the attached 4-conductor direct burial wire eliminates the water penetrability of a switch for low impedance/high impedance selection. With IP67 waterproof rating (pending), the Klipsch Pro-12SW-LS is lab tested and certified to offer the best in outdoor audio year in and year out.

### SPECIFICATIONS

FREQUENCY RESPONSE	29Hz - 125Hz +/- 3dB
SYSTEM TYPE	Band Pass Full Burial
WOOFER	12" (30.48cm) IMG Dual Voice Coil
SENSITIVITY	94 dB
POWER HANDLING	300W
IMPEDANCE	70V @ 150W 100V @ 300W 8 Ohm Stereo 4 Ohm Mono
ENCLOSURE MATERIAL	Canopy: Rustproof, UV Resistant Aluminum Cabinet: Heavy Duty, High Impact Polyethylene
FINISH	Canopy: Metallic Brown, Paintable Cabinet: Matte Black, Paintable
PRODUCT DIMENSIONS	25" x 16.14" x 26.42" (635mm x 410mm x 671mm)
PRODUCT WEIGHT	55 lbs (25 kg)
BUILT FROM	2016