

# PRO-500T-LS

## 5" LANDSCAPE SATELLITE

Part #1063137



### HIGH PERFORMANCE OUTDOOR AUDIO

With a 5" IMG woofer and a Tractrix horn-loaded 1" Aluminum Dome Tweeter, the Pro-500T-LS landscape satellite speaker uses the same high performance acoustic design philosophies of our legendary indoor products, bringing the world's most dynamic, powerful, detailed sound to your outdoor living space.

### ALL NEW TRACTRIX HORN

For decades, our proprietary Tractrix horn design has brought high efficiency, low distortion, and superb dynamics to every Klipsch product. By designing an all-new custom Tractrix horn for the PRO-500T-LS, we've been able to optimize those acoustic properties while providing ultra-wide 105° horizontal dispersion - for a powerful, balanced sound in every listening position.

### 8 OHM / 70V / 100V COMPATIBILITY

From small residential systems to massive commercial installs, the Klipsch Pro Series landscape speakers are designed to make any installation job quick and easy. For distributed line application, the Pro-500T-LS features a 30 watt, 70V/100V multi-tap transformer with 8 ohm bypass, allowing for perfect balance at any listening location, all selectable from a easily accessible, tool-free rotary switch on the back of the speaker.

### MAXIMUM INSTALL FLEXIBILITY

With both 18" and 10" ground stakes (sold separately), as well as a robust surface mount installation kit (coming soon), the Klipsch Pro-500T-LS landscape speaker can be installed - tool-free - in any commercial or residential outdoor space, making it the ideal solution for high quality audio in any outdoor entertainment or living area.

### ALL-WEATHER DURABILITY

A rustproof aluminum grille mated to a UV-resistant, mechanically reinforced ABS cabinet provides the utmost in all-weather capability, while a custom designed silicon switch cover on the back of the speaker prevents water penetrability. With IP67 waterproof rating (pending), the Klipsch Pro-500T-LS is lab tested and certified to offer the best in outdoor audio year in and year out.

### SPECIFICATIONS

FREQUENCY RESPONSE	70Hz - 20kHz +/- 3dB
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
LOW FREQUENCY DRIVER	5" (12.7cm) IMG Woofer
SENSITIVITY	87 dB
COVERAGE ANGLE	105°
POWER HANDLING	90W Peak
70V / 100V TAP SETTINGS	70V: 3.75W, 7.5W, 15W, 30W 100V: 7.5W, 15W, 30W 8 Ohm Bypass
ENCLOSURE MATERIAL	UV Treated High Impact ABS Cabinet
FINISH	Brown Matte, Paintable
PRODUCT DIMENSIONS	6.3" x 6.85" x 8.5" (160mm x 174mm x 216mm)
PRODUCT WEIGHT	5 lbs (2.27 kg)
ACCESSORIES	PRO-10-GS 10" Ground Stake (PN: 1063447)
BUILT FROM	2016